

Smart Pump G400-MP2

for G450/G460



- Optimised alarm system:
 - visual alarm via G450/G460 display and alarm LEDs
 - audible alarm via G450/G460 sounder
 - vibration alarm via G450/G460
- Enormous flexibility
(G450/G460 can be used in either pumped or diffusion mode)
- Autonomous power supply (does not take power from instrument)
- Sensor replacement without opening housing

Perfect interaction for maximum safety



G460 with pump activated:

- Sensor cover UP
- Diffusion inlets covered

Optimised alarm system

The new G400-MP2 pump communicates with the gas detectors G450/G460. This interaction allows fault indication via the detector display.

Low battery, blocked sampling line or interrupted power fault modes are shown on the display and activate different visual and audible warnings.

Various applications

Gas samples can be taken from distances of up to 100 m with considerable low-pressure performance – the safe solution for confined space measurement.

Enormous flexibility

The G400-MP2 is the only attachable pump available which may remain fixed to the detector. When the pump is turned on, the diffusion inlets are covered and the measurement results are not affected by air flows.

An additional filter system in the sampling line protects pump and sensors from dust and moisture. When the pump is turned off, the gas detector can be operated as usual. The diffusion inlets now allow all gases to enter the sensor chamber.



G460 with pump de-activated:

- Sensor cover DOWN
- Diffusion inlets open

Autonomous power supply

The G400-MP2 is operated on its own power supply, independently from the gas detector, i.e. the pump does not affect the operational time of the G450/G460. The pump power supply allows at least 10 hours of continuous operation.

Technical Data

Smart Pump G400-MP2

Pump performance:

0.50 l/min at 0 mm water column
0.25 l/min at 400 mm water column
max. low-pressure approx. 1600 mm water column
up to 100 m sampling distance

Dimensions :

109 x 68 x 21 (57) mm (HxWxD)

Electro-Magnetic Compatibility:

DIN EN 50270

Display and Alarm:

Audible, visual and vibration alarms communicated via G450/G460

LowFlow alarm:

Flow < 0.25 l/min

Protection:

IP40

Operational temperature/humidity:

-20°C ... +55°C; 5 ... 95 % r.h.

Storage temperature/humidity:

-25°C ... +55°C; 5 ... 95 % r.h.

Power supply options:

Alkaline batteries or rechargeable NiMH battery pack

Alkaline battery:

Approval:

ATEX Ⓜ II 2G Ex ia IIC T4/T3

Weight:

180 g

Operational time:

approx. 10 hours

NiMH battery:

Approval:

ATEX Ⓜ II 2G Ex ia IIC T4

Weight:

195 g

Operational time:

approx. 12 hours

Charging time:

< 4-5 hours



GfG Europe Ltd

Unit 8 | Griggs Business Centre
West Street | Coggeshall
CO6 1NT | Essex | UK

Tel.: +44 (0) 1376 561463
Fax: +44 (0) 1376 561704

www.gfgeurope.com
sales@gfgeurope.com